



 PRODUCT-DETAILS

ACS880-01-09A4-3

LV AC industrial wall-mounted single drive,
IEC: Pn 4 kW, 10 A, 400 V (ACS880-01-09A4-3)



General Information

Global Commercial Alias	ACS880-01-09A4-3
Product ID	3AUA0000107989
ABB Type Designation	ACS880-01-09A4-3
EAN	6438177558460

Catalog Description	LV AC industrial wall-mounted single drive, IEC: Pn 4 kW, 10 A, 400 V (ACS880-01-09A4-3)
---------------------	--

The ACS880-01 drives are customized to meet the particular needs of specific industries, such as oil and gas, mining, metals, chemicals, cement, power plants, material handling, pulp and paper, sawmills, marine, water and wastewater, food and beverage, and automotive. They can control a wide range of applications, including cranes, extruders, winches, winders, conveyors, mixers, compressors, centrifuges, test benches, elevators, extruders, pumps and fans.

Long Description

The ACS880-01 comes in one compact package for easy installation and commissioning. The drive can be installed on the wall as standard and in a cabinet as an option. The drive offering includes enclosure classes up to IP55, making it suitable for most environments and installations. ACS880-01 drives have all the essential features built-in. These features include as standard a choke for harmonic filtering as well as options like a brake chopper, EMC filter and communication protocol adapter, functional safety, external output filters and I/O extension modules.

Ordering

Customs Tariff Number	85044085
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS880-01-09A4-3 PN: 4.0 kW, IN: 10.0 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	7.0 kg 15.432 lb
Product Net Depth / Length	226 mm 8.898 in
Product Net Height	409 mm 16.102 in
Product Net Width	155 mm 6.102 in
Package Level 1 Depth / Length	574 mm 22.598 in
Package Level 1 Height	281 mm 11.063 in
Package Level 1 Width	256 mm 10.079 in
Package Level 1 Units	1 carton

Certificates and Declarations

Declaration of Conformity - CE	3AXD10000497831
REACH Date	20250320
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20240508
RoHS Information	3AXD10000497831
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Technical

Number of Phases	3-phase
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	4000 m 5 ... 95
Sound dB (A)	50 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 2 pcs, 6 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R1
Input Voltage (U _{in})	380 ... 415 V
Mounting Type	Wall-mounted

Communication Protocol

- CAN
- DeviceNet
- EtherNet/IP
- MODBUS
- Other Bus Systems
- PROFIsafe
- PROFIBUS
- PROFINET IO
- Industrial Ethernet 0
- Other 4
- Parallel 0
- PROFINET 0
- RS-232 0
- RS-422 0
- RS-485 1
- Serial TTY 0
- USB 1

Number of Hardware Interfaces

Includes

Control unit	2
PC connection	2
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 2
Output Current, Normal Use (I_n)	10 A
Output Current, Light-Overload Use (I_{LD})	9.5 A
Output Current, Heavy-Duty Use (I_{HD})	8.0 A
Output Power, Normal Use (P_n)	4 kW
Output Power, Light-Overload Use (P_{LD})	4.0 kW
Output Power, Heavy-Duty Use (P_{HD})	3.0 kW
Apparent Power Output	146 W
Efficiency Level	6.9 kV-A
Standby Loss	IE2
Complete Drive Module Efficiency (IEC61800-9-2)	23 W

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	65 W	0.9 %	84.8 %
0 / 50 %	79 W	1.1 %	89.9 %
0 / 100 %	114 W	1.6 %	92.0 %
50 / 25 %	69 W	1.0 %	91.7 %
50 / 50 %	86 W	1.2 %	94.5 %
50 / 100 %	126 W	1.8 %	95.6 %
90 / 50 %	93 W	1.3 %	96.6 %
90 / 100 %	146 W	2.1 %	97.1 %

Temperature Rating Maximum 40 °C

External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	41b0aacf-6aee-4855-80d0-b0b23674f3cc Finland
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Drives → Low Voltage AC Drives → Industrial Drives → ACS880 Single Drives → ACS880-01 - Wall-mounted single drive

