



 PRODUCT-DETAILS

ACS880-01-246A-3

LV AC industrial wall-mounted single drive,
IEC: Pn 132 kW, 246 A, 400 V (ACS880-01-246A-3)



General Information

Global Commercial Alias	ACS880-01-246A-3
Product ID	3AUA0000108031
ABB Type Designation	ACS880-01-246A-3
EAN	6438177554967

Catalog Description	LV AC industrial wall-mounted single drive, IEC: Pn 132 kW, 246 A, 400 V (ACS880-01-246A-3)
---------------------	---

The ACS880-01 drives are customized to meet the particular needs of specific industries, such as oil and gas, mining, metals, chemicals, cement, power plants, material handling, pulp and paper, sawmills, marine, water and wastewater, food and beverage, and automotive. They can control a wide range of applications, including cranes, extruders, winches, winders, conveyors, mixers, compressors, centrifuges, test benches, elevators, extruders, pumps and fans.

Long Description

The ACS880-01 comes in one compact package for easy installation and commissioning. The drive can be installed on the wall as standard and in a cabinet as an option. The drive offering includes enclosure classes up to IP55, making it suitable for most environments and installations. ACS880-01 drives have all the essential features built-in. These features include as standard a choke for harmonic filtering as well as options like a brake chopper, EMC filter and communication protocol adapter, functional safety, external output filters and I/O extension modules.

Ordering

Customs Tariff Number	85044086
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters
Invoice Description	ACS880-01-246A-3 PN: 132 kW, IN: 246 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	68.0 kg 149.914 lb
Product Net Depth / Length	386 mm 15.197 in
Product Net Height	965 mm 37.992 in
Product Net Width	300 mm 11.811 in
Package Level 1 Depth / Length	1145 mm 45.08 in
Package Level 1 Height	654 mm 25.75 in
Package Level 1 Width	485 mm 19.09 in
Package Level 1 Units	1 case

Certificates and Declarations

Declaration of Conformity - CE	3AXD10000497831
REACH Date	20250320
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20240508
RoHS Information	3AXD10000497831
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Technical

Number of Phases	3-phase
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	4000 m 5 ... 95
Sound dB (A)	68 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 2 pcs, 6 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R8

Input Voltage (U_{in})	380 ... 415 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIsafe PROFIBUS PROFINET IO
Number of Hardware Interfaces	Industrial Ethernet 0 Other 4 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 2
Output Current, Normal Use (I_n)	246 A
Output Current, Light-Overload Use (I_{LD})	234 A
Output Current, Heavy-Duty Use (I_{HD})	206 A
Output Power, Normal Use (P_n)	132 kW
Output Power, Light-Overload Use (P_{LD})	132 kW
Output Power, Heavy-Duty Use (P_{HD})	110 kW
Apparent Power Output	3026 W
Efficiency Level	170 kV·A IE2
Standby Loss	52 W
Complete Drive Module Efficiency (IEC61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	767 W	0.4 %	92.4 %
0 / 50 %	1105 W	0.6 %	94.2 %
0 / 100 %	1952 W	1.1 %	94.7 %
50 / 25 %	826 W	0.5 %	95.9 %
50 / 50 %	1208 W	0.7 %	96.8 %
50 / 100 %	2281 W	1.3 %	97.0 %
90 / 50 %	1432 W	0.8 %	97.9 %
90 / 100 %	3026 W	1.8 %	97.8 %

Temperature Rating	Maximum 40 °C
--------------------	---------------

External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	f10203a7-c2ae-4d29-a475-9eef0fd6d938 Finland
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Drives → Low Voltage AC Drives → Industrial Drives → ACS880 Single Drives → ACS880-01 - Wall-mounted single drive

