

TSXETG1010

web gateway module - 8 MB - class C20 -
access to Uni-Telway device variables



Main

Range of Product	FactoryCast Gateway
Product or Component Type	Web gateway module
Concept	Transparent Ready
Memory capacity	8 MB
Web server	Class C20

Complementary

Communication gateway	Ethernet TCP/IP to Modbus Routing to I/O scanning service Modem to Ethernet TCP/IP with IP routing/RAS server (remote access server) Modem to Modbus
Web services	Access to Uni-Telway device variables standard Configuration via predefined web pages standard Diagnostics via predefined web pages standard File upload/download via FTP configurable Hosting of animated web pages configurable HTTP server configurable Library of graphic objects configurable Alarm notification by e-mail
Internal processing	Security miniature firewall on-board SMTP client SNMP agent FTP server BootP/DHCP protocol PPP protocol
[Us] rated supply voltage	24 V DC
Supply voltage limits	9...30 V DC
Line Rated Current	0.1 A
Integrated connection type	Ethernet TCP/IP RJ45, 10...100 Mbit/s, 1 twisted pair Serial link modem male SUB-D 9 PPP, PAP authentication RS232C, half or full duplex, 57 kbit/s Serial link RJ45 Uni-Telway and/or Modbus TCP slave RS485, 19.2 kbit/s
Maximum Number of Connected Devices	Serial link <32
Port Ethernet	10BASE-T/100BASE-TX
Mounting Support	Symmetrical DIN rail Plate
LED indicators	For Ethernet activity (Ethernet) 1 LED (green) For Uni-Telway activity (RUN/UTW) 1 LED (green) For gateway error (ERR) 1 LED (red)
Width	1.57 in (39.83 mm)
Height	5.96 in (151.5 mm)
Depth	5.22 in (132.7 mm)
Net Weight	0.62 lb(US) (0.28 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for operation	32...140 °F (0...60 °C)
Relative Humidity	10...95 % without condensation
IP Degree of Protection	IP20
Standards	CSA C22.2 No 213 Class I Division 2 UL 508 ANSI/IEEE Std 802.3 EN 55011 class A ISO/IEC 8802-3 CSA C22.2 No 142 EN/IEC 61131-2 EN 61000-6-4


Ordering and shipping details

Category	18225 - PLC NTRK HRDWR & PROWORX SOFTWARE
Discount Schedule	PC41
GTIN	3595863867428
Nbr. of units in pkg.	1
Package weight(Lbs)	23.74 oz (673 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.36 in (6 cm)
Package 1 width	6.89 in (17.5 cm)
Package 1 Length	10.24 in (26 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Weight	17.80 lb(US) (8.076 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	18 months
----------	-----------